



# SP 510



## POWERFUL, WIDE-OPENING SPREADER.

The SP 510 is used for the most difficult rescues worldwide. Its high force, very wide opening and intuitive use permits quick and safe rescue work on vehicles (car, truck, bus, tram) or during events resulting in major damage such as natural disasters.

Spreaders

### Advantages

- + Peel away steel walls up to approx. 0.16 in./4 mm thick
- + Create rescue openings up to 31.5 in. x 31.5 in./80 cm x 80 cm
- + Spreading, peeling, squeezing and pulling without the need to change tips

### Accessories

#### KSV 11 chain set

**Length** 2 x 6.6 ft./2 x 2 m

#### KSS 20 quick-fit chain set

**Length** 2 x 7 ft./2 x 2,2 m

Technical data	SP 510
Spreading force	13,940 - 51,710 lbs/62 - 230 kN
Spreading distance	31.5 in./800 mm
Squeezing force	15,800 lbs/70.4 kN
Pulling distance	26.2 in./665 mm
Pulling force up to	12,365 lbs/55 kN
Oil requirement	25.9 cu. in./425 cm <sup>3</sup>
Dimensions: l x w x h	35.4 x 15 x 8.5 in/900 x 380 x 215 mm
Weight	55.1 lbs/25 kg
Certification	NFPA 1936
EN-Classification	BS 62/800 - 25

WEBCODE: qpaies