

## VOLVO FLL 4X2 FACTORY FIT CREWCAB *(North Yorkshire F&RS Specification)*

### Summary

- B type water Tender.
- 1800 litre water capacity.
- Volvo 4x2 chassis.
- 6 person safety crew cab.



### Outline Specification

#### Chassis Specification

- Volvo 15.260 FLL 4100mm wheel base – option for 4400mm wheel base available.
- Volvo factory fit crew cab with 300mm extension (150mm extension available) painted to customer specification.
- Parabolic front springs with shock absorbers and anti roll bar. Two bag rear air suspension
- Gross vehicle weight 15000kg.
- Engine output – D7F290 7.2l engine developing 260hpMax torque 1070Nm at 1200-1800rpm. Euro 5 Mandatory engine emission level. (options available).
- Allison 3000 series automatic 6-speed transmission Hydraulic Retarder
- Power take off Chelsea top mount PTO – option available to suit fire pump installation.
- Tyres - Front tyres: 285/70R19.5 M Bridgestone R227 long distance steer pattern. Drive tyres: 285/70R19.5 M Bridgestone R227 long distance steer pattern.

#### Body Specification

- Emergency One PP Copolymer bodywork – option for GRP & aluminium built bodies available.
- Integrated 1800 water tank – capacity to customer specification (foam tank option available).
- Stowage to suit customer specification – options can be obtained on request.
- X6 side locker c/w JR industry RSDs.
- Locker width dimensions – Front=1440mm / rear=1275mm / rear=1400mm.
- 750mm width full through locker for extra depth shelving.
- Optional wing pockets for spare BA's.
- Integrated air intake cavity on OSF on body bulkhead.

#### Accessories

- Emergency One standard wiring harness installation.
- Hale Godiva Prima P2A 2010 with built in Collecting head. C/w 3 Continental delivery valves fitted with crank handle (2000 litres per minute). 3010 & 4010 options available.
- 24V lighting mast c/w 2 or 4 way LED lighting. Position optional.
- Ladder Gantry Package for 464 Ladder (13.5m T/Ext'n) c/w counter balance tilt-head gantry (pneumatic option available).
- Beam Gantry to suit 9m Double Extension ladder c/w Stainless Steel T-Handle.
- Beam Gantry to suit 20ft folding Roof Ladder c/w Stainless Steel T-Handle.
- X2 55m hose reels mounted high in middle lockers – hose capacity & position variable.
- Emergency One's ePump control, In-Cab Status monitor & Data Logger options available.
- Cab has 4 forward facing BA seats c/w storage for masks and helmets. (See products for options).

DATA-032/a



Further Options available.  
To discuss, please contact Emergency One:

Tel : 01290 424200 / 423815  
Fax : 01290 423834

Email : [enquiries@emergencyone.co.uk](mailto:enquiries@emergencyone.co.uk)