



PORTABLE BREACH PACK

Part #6001

The Portable Breach Pack is a transportable system designed for compact tactical hot cutting operations. The system provides operators with all the components necessary to conduct operations with Petrogen. The system also includes a filler pigtail, which allows operators to trans-fill the included 23 cubic foot oxygen bottle from a larger oxygen supply. A medical yoke adapter, used to connect a CGA 540 oxygen regulator on a CGA 870 valve, and a carry case which holds all the systems central parts including a torch and Heavy Duty Igniter bracket.

System Contents

- Torch (7 inch, 75 degree)
- (10) Cutting Tips (two 0, two 1, two 2, two 81, & two 83)
- Liquid Fuel Hose (20 foot)
- Oxygen Hose (20 foot)
- Liquid Fuel Tank (2 quart)
- (2) Fuel Quick Disconnects
- (2) Oxygen Quick Disconnects
- Oxygen Flashback Arrestor
- 23 Cubic Foot CGA 540 Industrial Oxygen Bottle
- Medium Duty Oxygen Regulator (CGA 540)
- Spark Striker
- Carry Case
- Filler Pigtail
- Medical Yoke Adapter
- Spare Parts Kit (see list for contents)
- Tool Kit (see list for contents)
- Adjustable Wrench
- Protective Glasses
- Welding Gloves
- Reference Manual & Training Video



Usable Fuels:

- Gasoline (any grade)
- White Gas
- Camping Fuel
- Stabilizer Additive Fuels
- * Diesel
- * Bio-diesel
- * Kerosene
- * Jet-A, JP-8, JP-5 and JP-24

* Torch requires the addition of the Multi-Fuel Adapter Kit.

The Portable Breach Pack Carry Case holds a 23 Cubic Foot CGA 540 Oxygen Bottle which allows for:

- **25 min. of cutting on 1/4 in. steel**
- **13 min. of cutting on 1 in. steel**
- **5 min. of cutting on 4 in. steel**



PT Rescue

19 Ricketts Rd,
Mt Waverley,
VIC 3149

P: +61 3 9562 8800

F: +61 3 9562 8080

E: rescue@pthydraulics.com.au



Tip Selection Chart

STANDARD		Pounds / Inches ²	
Tip No.	Inches	Fuel	Oxygen
0, HHO	0 - ¼	10 - 20	12 - 17
1, 81, HH1	¼ - 1	10 - 20	17 - 25
2, HH2	1 - 2	10 - 20	25 - 35
3, 83, HH3	2 - 4	10 - 20	35 - 40
4, HH4	4 - 6	12 - 20	40 - 50
5, HH5	6 - 8	14 - 20	50 - 60
6, HH6	8 - 10	16 - 20	70 - 80
7	10 - 12	18 - 20	80 - 100
8	12 - 14	20	120+
L	Heating	18-20	100

- Tip sizes 81 and 83 are “scrapping” tips. They both have the pre-heating capabilities of our largest tip, tip size 8. This encourages faster preheat through rust, dirt and paint. The 81 has the cutting capabilities of our tip size 1, and the 83 has the cutting capabilities of our tip size 3.
- High Heat Tips (Part #HH0-HH6) are designed for use with the Multi-Fuel Adapter (Part #8000).

Head Angle Options

- 75° - Is commonly selected for the 36 inch or 48 inch torch. This angle is mostly used where the torch operator needs reasonable standoff distance and the material being cut is located on the ground.
- 90° - Is the angle mostly used where the torch operator needs to cut a material that runs parallel to the torch.
- 180° - Is the angle commonly used by machine torches and operators performing cuts on walls or overhead.

Lifetime Warranty

Any Petrogen product found to be defective in materials or craftsmanship will be repaired or replaced at no charge during the warranty period (25 Years).

Tool Kit Part #4003

- Packing Nut Wrench (Part #4011)
- Tip Reamer (Part #4012)
- Two Part Tip Brush (Part #4013)
- Jackscrew (Part #4016)
- Tip Drill Set (Part #4018)
- Hex Allen Wrench (Part #4019)

Spare Parts Kit Part #4002

- Preheat Oxygen Valve (Part #1300)
- H.P. Oxygen Valve (Part #1350)
- H.P. Valve Ext. O-rings (Part #1356)
- H.P. Valve Int. O-rings (Part #1357)
- Lever Nut (Part #1403)
- Lever Screw (Part #1404)
- Mixer Assembly (Part #1800)
- (2) Metal Wicks (Part #1802)
- Mixer Lrg. O-ring (Part #1803)
- Mixer Sml. O-ring (Part #1356)
- Filler Cap Gasket (Part #2157)
- Leather Pump Cup (Part #2327)
- Check Valve Flat Seal (Part #2306)
- O-ring Installation Tool (Part #4017)
- Extra Flint for Sparker (Part #4021)

Other

- Multi-Fuel Adapter Kit
Part #8000
- Air Pressure Regulator Kit
Part #2348
- Compressed Air Carry Tank
Part #2365
- Hand Cart
Part #4560

