



Rescue paths

Ensuring stability and safety in dangerous situations.

Rescue paths

Providing sure footing on all surfaces.

- › Ready for application in seconds
- › Flexibly expendable
- › Easy handling
- › Anti-slip surface

Always retain sure footing – even on unstable ground! With Vetter rescue paths, your team can walk safely across stretches of water, ice, moorland and bog. The rescue paths require very little compressed air and are ready to deploy in seconds. The three standard lengths of 6, 10 and 15 metres (19.2 ft., 32 ft. and 48 ft.) can be connected, so you will be prepared for any emergency scenario. The convenient anti-slip strips provide your team with a firm grip to safely rescue people who are drowning or sinking.



Safe walking on anti-slip strips



Sure footing on the water surface



Rescue path for emergency rescue at sea*

Technical data*

| Rescue paths with anti-slip strips | Ext. dimensions (L x W x H) cm / inch | Air requirement at 0.5 bar (7.25 psi) litres / cu. ft. | Inflating time, approx. sec. | Folded size (L x W x H) cm / inch | Weight, approx. kg / lbs |
|------------------------------------|---------------------------------------|--|------------------------------|-----------------------------------|--------------------------|
| 6 m 1530008502 | 600 x 140 x 10 236 x 55 x 4 | 1,321 47 | 18 | 165 x 35 x 25 65 x 14 x 10 | 28.3 62.5 |
| 10 m 1530008602 | 1,000 x 140 x 10 394 x 55 x 4 | 2,196 78 | 30 | 165 x 45 x 30 65 x 18 x 12 | 45.4 100 |
| 15 m 1530008702 | 1,500 x 140 x 10 591 x 55 x 4 | 3,360 119 | 45 | 165 x 60 x 45 65 x 24 x 18 | 67.5 149 |

Rescue paths:
Working pressure: 0.5 bar (7.25 psi)
Test pressure: 0.65 bar (9.4 psi)

**Load capacity approx. 95 kg / m²
(19.54 lbs / sq. ft.)**

*Technical changes reserved.

Accessories

Inflation hose, 500 mm (20 inch), for direct inflation from compressed air cylinder



1530003401
1530007600 (USA)

Compressed air cylinder



6 l / 300 bar, (0.21 cu. ft. / 4,350 psi) steel, 5/8" IT, 1,800 l (63.5 cu. ft.)

1600010800

9 l / 300 bar, (0.32 cu. ft. / 4,350 psi) composite, 5/8" IT, 2,700 l (95.3 cu. ft.)

1600019900

Vacuum adapter for safety cushions and rescue paths

Attach quick action coupling to air source, the pressure should be between 4 and 6 bar (58 and 87 psi).



1600016300



In operation ...

- › Rescuing people who are drowning or who have fallen through ice
- › Rescue missions on unstable ground
- › Traversing stretches of water or boggy ground
- › Emergency sea rescue



Good reasons:

- › Inflated and ready to use in seconds
- › Several paths variably connectable
- › Optimum edge profile for pulling persons on board



Guaranteed quality:

- › Individually tested (with inspection seal)
- › Integrated safety valve prevents overinflation
- › Tear-proof material

