

# SP 777

THE NEW STANDARD IN THE  
HIGH PERFORMANCE CLASS.



Scan this QR code  
for further information.



## SP777

Our Shooting-Stars SP333 and SP555 now have a big brother: the hose bound high performance spreader SP777. Its breathtaking spreading force of up to 600 kN, a spreading width of an incredible 813 mm and relentless “Shark Tooth” tips make it the ultimate rescue spreader for vehicle accidents (cars, trucks, buses, trains, trams) or after large-scale emergencies such as natural disasters. But that’s not all: This powerhouse weighs just 19.7 kg – a whole 5 kg less than its SP510 predecessor model. This makes the SP777 the lightest BS spreader currently on the market!

### “SHARK TOOTH” TIPS

The right grip for spreading when every second counts: the design of the specially developed “Shark Tooth” tips and their arrangement in 3 rows guarantee maximum performance!



### Advantages

- + Spreading, peeling and pulling without changing tips
- + Extremely short opening and closing times for rapid and safe rescue
- + With a weight of 19.7 kg, a whole 5 kg lighter than the previous SP510 model!
- + Biting performance thanks to innovative “Shark Tooth” tips
- + Intuitive handling even under severe time pressure

### Accessories



KSV 11 chain set

<b>Length</b>	2 x 6.6 ft./2 x 2 m
---------------	---------------------

Technical data	SP777
Spreading force	14,160 - 134,900 lbf./63 - 600 kN
Spreading distance	32.0 in./813 mm
Squeezing force up to	27,400 lbf./122 kN
Pulling force up to	13,490 lbf./60 kN
Pulling distance	25.8 in./655 mm
Oil requirement	23.5 cu. in./385 cm <sup>3</sup>
Dimensions: l x w x h	35.4 x 12.2 x 7.95 in./898 x 309 x 202 mm
Weight	43.4 lbs./19.7 kg
Certification	NFPA 1936
EN classification	BS 63/813-19,7