

e³ – SPREADERS

SP 333 e³ / SP 555 e³ / SP 777 e³



SP 333 e³

SP 555 e³

SP 777 e³



1 **DASHBOARD** with performance diagnostics displays

2 **LEDs** directed towards the tool head for optimum illumination

3 Flexible **ALL-ROUND GRIP** for variable positioning of the spreader

4 **SHARK-TOOTH-TIPS** with aggressive grip for every material

5 **EXTRA-FLAT TIPS** for narrow gaps

	SP 333 e ³	SP 555 e ³	SP 777 e ³
Article number	93-10-13	93-10-23	93-10-31
Spreading force up to	836 kN	658 kN	600 kN
Spreading force 25 mm tip inwards (EN)	42 kN	52 kN	63 kN
Spreading travel	600 mm	730 mm	813 mm
Crushing force up to	144 kN	115 kN	122 kN
Pulling force	56 kN	58 kN	60 kN
Pulling travel	440 mm	569 mm	655 mm
Dimensions ¹⁾	823 x 256 x 253 mm	923 x 265 x 253 mm	997 x 309 x 253 mm
Weight ²⁾	17.1 kg	19.9 kg	23.4 kg
Protection class	IP 58	IP 58	IP 58

¹⁾ L x W x H ²⁾ excluding power supply unit or battery