

# POWER UNITS

P 635 SG / P 635 SG DHR 20 / P 635 SG DHR-COAX  
PETROL ENGINE



# POWER UNITS

P 635 SE / P 635 SE DHR 20 / P 635 SE DHR-COAX  
ELECTRIC MOTOR



	P 635 SG	P 635 SG DHR 20	P 635 SG DHR-COAX
Article number	81-53-40	81-54-43	81-54-40
Engine	4-stroke petrol engine	4-stroke petrol engine	4-stroke petrol engine
Connection	2 tools	2 tools	2 tools
Operation	2 tools	2 tools	2 tools
Turbo function	included	included	included
Max. output	2.4 kW	2.4 kW	2.4 kW
Max. operating pressure	700 bar	700 bar	700 bar
Delivery rate Low/high pressure	2 × 3.0–2 × 0.79 l/min	2 × 3.0–2 × 0.79 l/min	2 × 3.0–2 × 0.79 l/min
Turbo delivery rate Low/high pressure	1 × 5.8–1 × 1.53 l/min	1 × 5.8–1 × 1.53 l/min	1 × 5.8–1 × 1.53 l/min
Usable oil quantity	5 l	5 l	5 l
Dimensions <sup>1)</sup>	440 × 440 × 445 mm	798 × 440 × 600 mm	820 × 440 × 600 mm
Weight <sup>2)</sup>	32.7 kg	72.7 kg	74.5 kg
Hose length	–	2 × 20 m double hose	2 × 20 m mono-hose
Certification	EN 13204, NFPA 1936	EN 13204, NFPA 1936	EN 13204, NFPA 1936

<sup>1)</sup> L x W x H <sup>2)</sup> incl. petrol for 1 hr and 4.3 l hydraulic oil

	P 635 SE	P 635 SE DHR 20	P 635 SE DHR-COAX
Article number	81-53-41	81-54-44	81-54-41
Engine	230 V electric motor	230 V electric motor	230 V electric motor
Connection	2 tools	2 tools	2 tools
Operation	2 tools	2 tools	2 tools
Turbo function	included	included	included
Max. output	2.2 kW	2.2 kW	2.2 kW
Max. operating pressure	700 bar	700 bar	700 bar
Delivery rate Low/high pressure	2 × 2.4–2 × 0.55 l/min	2 × 2.4–2 × 0.55 l/min	2 × 2.4–2 × 0.55 l/min
Turbo delivery rate Low/high pressure	1 × 4.7–1 × 1.24 l/min	1 × 4.7–1 × 1.24 l/min	1 × 4.7–1 × 1.24 l/min
Usable oil quantity	5 l	5 l	5 l
Dimensions <sup>1)</sup>	440 × 440 × 445 mm	798 × 440 × 600 mm	820 × 440 × 600 mm
Weight <sup>2)</sup>	36.7 kg	76.7 kg	78.5 kg
Hose length	–	2 × 20 m double hose	2 × 20 m mono-hose
Certification	EN 13204, NFPA 1936	EN 13204, NFPA 1936	EN 13204, NFPA 1936

<sup>1)</sup> L x W x H <sup>2)</sup> incl. 4.3 l hydraulic oil